

Section 4-7 MULTIPLE-FAMILY RESIDENTIAL DISTRICTS - MR-5

4-7.1 INTENT

The MR-5 Multiple-Family Residential District is intended to establish and preserve neighborhoods containing predominately multiple family dwellings. These dwellings will be built at a density equal to or greater than that permitted in the MR-4 districts. This district is also intended to promote the development of comparable new areas and the uses compatible with such developments.

4-7.2 PERMITTED USES

APARTMENTS

CONDOMINIUMS

DAY CARE CENTERS: Day Family Care Home; Day Group Care Center, Class A & Class B

GROUP HOMES: Family Group Home; Group Home Center, Class A & Class B

LIBRARY

MULTIPLE-FAMILY DWELLINGS

TOWN HOUSES

4-7.3 SPECIAL USES

BOARDING HOUSE, ROOMING HOUSE

CHURCHES and other places of formal worship

COMMERCIAL ESTABLISHMENTS serving primarily the inhabitants of the District

HEALTH CARE/SERVICE ESTABLISHMENTS serving the inhabitants of the district or requiring a residential type setting, such as a nursing/convalescence home

4-7.4 LOT & STRUCTURAL REQUIREMENTS

In districts zoned MR-5, unless approved as a Planned Unit Development, every principal building shall conform to the following requirements:

- | | |
|---------------------------------------|---------------|
| A) Minimum Lot Area | 7,500 Sq. Ft. |
| 1) Minimum Lot Area per Dwelling Unit | 2,500 Sq. Ft. |
| B) Minimum Lot Width | |
| 1) At the established building line | 75 Feet |
| D) Minimum Lot Depth | None |

| | |
|-------------------------------------------------------|----------------|
| E) Minimum Set Backs | |
| 1) From front lot line | 25 Feet |
| 2) From any side lot line | 10 Feet |
| 3) From rear lot line | 25 Feet |
| 4) From principal structure on adjacent lot | 20 Feet |
| 5) From corner lot line on both street frontages | 25 Feet |
| 6) Accessory Buildings | |
| a) From principal building | 10 Feet |
| b) From rear lot line | 8 Feet |
| c) From side lot line | 5 Feet |
| d) Maximum structure height | 15 Feet |
| e) Maximum percentage of rear yard coverage | 30% |
| f) Limit two (2) per lot | |
| g) Distance between structures | 5 Feet (14-06) |
| F) Maximum Structure Height | 50 Feet |
| G) Maximum Floor Area Ratio | 1.5 |
| H) Maximum Percentage of Lot Coverage | |
| - Including accessory buildings | 50% |
| I) Minimum Floor Area per Dwelling Unit - First Level | 400 Sq. Ft. |

4-7.5 OFF-STREET PARKING & LOADING REQUIREMENTS

4-7.5(A) Location:

A) Parking spaces accessory to dwellings located in this district shall be located on the same lot as the dwelling. Such parking spaces shall not be located in any required front yard except in a driveway, but may be located in the side or rear yards. Each parking space shall be unobstructed so that no vehicle need be moved in order to allow another vehicle to enter/exit the parking area.

B) All parking spaces accessory to permitted non-dwelling uses located in this district generally shall be located on the same lot as the use serviced. However, such parking facilities may be located on another parcel within two-hundred feet of the use served if the "same lot" requirement is not feasible.

C) No commercial vehicle exceeding one ton cargo capacity shall be parked anywhere in this district except for normal loading, unloading, and service calls.

4-7.5(B) Minimum Required Number of Spaces:

All dwellings located within this district shall have a minimum of two parking spaces per dwelling unit. No loading space is required.

Any uses developed within this district are required to provide parking spaces and loading space as outlined in Article 6.